



TENSIÓN ASIGNADA <i>RATED VOLTAGE</i> TENSION ASSIGNÉE	Ur	kV	36	
FRECUENCIA ASIGNADA <i>RATED FREQUENCY</i> FRÉQUENCE ASSIGNÉE	Fr	Hz	50/60	
NIVEL DE AISLAMIENTO <i>INSULATION LEVEL</i> NIVEAU D'ISOLEMENT			VALOR COMÚN COMMON VALUE VALEUR COMMUNE	A SECCIONAMIENTO ACROSS ISOLATING A SECTIONNEMENT
ONDA DE CHOQUE 1.2/50µs <i>LIGHTNING IMPULSE 1.2/50µs</i> ONDE DE CHOC 1.2/50µs	Up	kVpk	185	215
FRECUENCIA INDUSTRIAL 50Hz 1min <i>POWER FREQUENCY 50Hz 1min</i> FRÉQUENCE INDUSTRIELLE 50Hz 1min	Ud	kV	90	118
INTENSIDAD ASIGNADA TUBO PORTAFUSIBLES <i>ASSIGNED INTESITY FUSE HOLDER TUBE</i> COURANT ASSIGNÉ TUBE PORTEFUSIBLE	Ir	A	100 (*)	
INTENSIDAD ASIGNADA BASE CUTOUT <i>RATED CURRENT</i> COURANT ASSIGNÉ	Ir	A	200	
INTENSIDAD ADMISIBLE DE CORTA DURACIÓN <i>SHORT TIME WITHSTAND CURRENT</i> COURANT DE COURTE DURÉE	Ik	kA	8	
VALOR CRESTA CORRIENTE ADMISIBLE <i>PEAK WITHSTAND CURRENT</i> VALEUR CRÊTE DU COURANT	Ip	kApk	20 / 20.8	
LÍNEA DE FUGA <i>CREEPAGE DISTANCE</i> LIGNE DE FUITE	Lf	mm	730	

(*) Para otros valores consultar / for other values consult.
Pour autres valeurs consulter.

NORMAS <i>STANDARDS</i> NORMES	IEC 62.271 - 1 IEC 60.282 - 2 ANSI C 37.42 UNE 21120 - 2
DIMENSIONES EMBALAJE UNITARIO <i>UNIT PACKING DIMENSIONS</i> DIMENSIONS UNITE D'EMBALLAGE	(mm)
LONGITUD <i>LENGTH</i> LONGUEUR	450
ANCHO <i>WIDTH</i> LARGEUR	170
ALTURA <i>HEIGHT</i> HAUTEUR	750
PESO <i>WHEIGHT</i> [kg] POIDS	Kg
EQUIPO <i>DEVICE</i> APPAREIL	13.5
CANTIDAD POR PALET <i>AMOUNT BY PALLET</i> MONTANT PAR PALETTE	14 Ud.
DIMENSIONES EMBALAJE PALET <i>PALLET PACKING DIMENSIONS</i> DIMENSIONS EMBALLAGE PALETTE	(mm)
LONGITUD <i>LENGTH</i> LONGUEUR	1200
ANCHO <i>WIDTH</i> LARGEUR	800
ALTURA <i>HEIGHT</i> HAUTEUR	1125



iberapa

MASAMAGRELL (VALENCIA) ESPAÑA

IA

C710713/ZBHF

Año fab.Nº

Ur

36

kVIr

200

A

Up

185

kVlk

8

kA

Ibérica de Aparellajes S.L. fr = 50 / 60 Hz

(*) Para otros valores consultar / for other values consult.
Pour autres valeurs consulter.