





NOUVEAU

Couvercle L45 - Clippage Direct

RoHS

IP44

L x H (mm)		Profil	Réf.	Caractéristiques des Goulottes				Capacité des Câbles Isolés					
				Dim. Intérieures	Longueur	Section Intérieure (S)	Section Utile (Su)	ø Utile Max.	N ^{bre} Max. Conducteurs H07 V-U				
				(mm)	(m)	(mm ²)	(S/1,4) (mm ²)	(mm)	1,5 mm ²	2,5 mm ²	4 mm ²	6 mm ²	
100 x 50			11020 CBR	96x47	2,00	2155	1539	32	191	135	106	81	
						① 493 ② 1058 ③ 493	352 756 352	20 32 20	43 94 43	31 66 31	24 52 24	18 40 18	
155 x 50			11030 CBR	75x47 75x47	2,00	① 1672 ② 1672	1194 1194	32 32	148 148	105 105	82 82	63 63	
						① 357 ② 1259 ③ 1259 ④ 357	255 899 899 255	16 32 32 16	31 111 111 31	22 79 79 22	17 61 61 17	13 47 47 13	
190 x 50			11040 CBR	63x47 57x47 63x47	2,00	① 1325 ② 1214 ③ 1325	946 867 946	32 32 32	117 107 117	83 76 83	65 59 65	50 46 50	

CBR - Complet Blanc.

NOTE: Couvercle de largeur de 45 mm (L45).